

FLOS

03.8005.14.DA Black

Light Stripe 300 mm Dali Version


Designed by FLOS Architectural, 2017



Diffused LED light module to be installed in The Tracking Magnet System.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
LED type	Top LED
Lamp category	LED
Ilcos	No
Bulb finish	Clear
Number of heads	1
Power (W)	6
System power (W)	6
Source flux (lm)	533
System flux (lm)	202
Efficacy (lm/W)	33.67

Physical

Colour	Black
Trim	No
Orientation	Fixed
Length (mm)	300
Net weight (kg)	0.1
IP internal	20
IP external	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[↓ ZIP](#) Bim



Schematic light drawing



Ecodesign and Energy Labelling



Replaceable (LED only)
light source by a
professional



Replaceable control
gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	2
LED Life / Failure Ratio	L80B50
Beam angle C0-180 (°)	109
Beam angle C90-270 (°)	109

Electrical

Insulation class	III
Forward voltage (V)	48
LED current (mA)	130
Driver	Remote excluded
Dimmable	Yes
Dimming type	Dimmable DALI 2
Dimming range (%)	20-100
Dimming interface	Remote Dimmable (Dimmer Not Included)
Emergency type	No

Notes

Opal end covers not included. They must be ordered separately (08.0125.00 includes two units). Only compatible with DALI profile version. For wireless lighting control, choose integrated Casambi versions.