



DEEP ASYM

CEILING RECESSED



p. 587



1.0 LED

LED 7/10W | 350/500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.25kg IP20 35° 100 4-30

87 35°/35° 355° 100 4-30

Color	CODE
White	112461W
Grey	112461S
Gold	112461G
Black	112461B

Light Colour Selection

LUMEN	CRI	CODE
2700K	450/610	>90 3
3000K	470/640	>90 5
1800-2850K	16V 290/390	>95 9

ALWAYS USE

power supply

Specs	CODE
350mA 10W	90223401
500mA 10W	90214404
500mA 15W dim	90224501

more power supplies on page 588



1.0 MR16

QR-CBC51 max.35W | GU5.3
12V | excl. power supply
aluminium powder coated

0.19kg IP20 35° 90 4-30

87 35°/35° 355° 90 4-30

Color	CODE
White	112410W0
Grey	112410S0
Gold	112410G0
Black	112410B0

ALWAYS USE

power supply

Specs	CODE
12V 10W dim	90221401
12V 25W dim	90221701
12V 70W dim	90221904

more specs on page 591



1.0 PAR16

PAR16 max.12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

0.23kg IP20 35° 115 4-30

87 35°/35° 355° 115 4-30

Color	CODE
White	112420W0
Grey	112420S0
Gold	112420G0
Black	112420B0

OPTIONAL

PAR16 LED GU10 7W
phase-cut dim

Specs	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 593