## Algorithm




Design By Toan Nguyen



## Model Sheet







Optional: Extra cable length Min. quantity, upcharge and extra lead time apply [EN]

Finish

93 White RAL 9016



18 Graphite ADAPTA RF 9913 WX

LED temperature color

2700 K / 3000 K / 3500 K

Dimmina

DALI 1-10V Push / CASAMBI

Instalation type

Surface Canopy

Materials

Sphere: Blown glass Glass fastening: Aluminum Diffuser: Polycarbonate Pendant structure: Steel

Light source

24 x LED 3,15W 1050mA

LED

CRI>80 7495 lm 99 2700 K / 3000 K / 3500 K

Driver

Constant Current 1050 100~240 V V 50~60 Hz HZ

Remarks

Request built-in canopy at www.vibia.com

The steel cables that go from the structure to the ceiling are the only ones that allow the height of the lamp to be adjusted. The installation manual describes how to do this and how to cut the

cables.





IP20 Bi-volt 50-60Hz

**Application** 

Hanging lamps

**Packaging** 

2 Box

1.689 m x 1.689 m x 0.18 m Gross weigth 30.4 Net weigth 26.3

Vol. 0.7268

Lighting effect

**General Lighting** 

Lamp for general lighting that equally distributes the light in all directions



Photometric Data

**Total Flux** 

7495 lm

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty