BREAK

Design by Xucla & Alemany.



Reference

4106.

Application

Outdoor lamps

Installation type

Surface

Description

Outdoor bollard light designed by Xuclà & Alemany. It gives a pleasant, subtle light through the methacrylate diffuser, and can withstand tough outdoor conditions. Available in khaki lacquer, oxide lacquer and concrete.

Diffuser

Methacrylate diffuser

Materials

Head: Polyurethane Base: Polyurethane Diffuser: Methacrylate

Finish



4106-07 Khaki lacquer (RAL 7006)




4106-54 Oxide lacquer (RAL 8014)



4106-80 Concrete (Acabado natural)

Sketch



Electrical characteristics

1 x LED 6,2W 350mA





Total 6.2 W





Led 2700K CRI >80 580 Im 94 Im/W

Fixture: 218 lm 35 lm/W

Driver included: CC - Constant Current 350 mA 100-240V 50/60Hz

Electronic dimming ${\sf NO\ DIM}$

Physical characteristics

1 Box / 0.51 x 0.34 x 0.35 m. / Vol. 0.0598 m^3 / Gross weight 7.6 kg. / Net weight 6.8 kg.

Installation and assembly

Please, see the installation manual


Light distribution

Ground lighting

Reduced-height outdoor lamp to shade light on the ground.



Photometric data



Certificates







