

## HOLLOW 115 TRIMLESS LED GE


For designer James Van Vossel, it was time to rethink pure, simple forms. That's when the tube came in. And out. Hollow reignites the excitement and mystery surrounding this classical shape. How does it work? Where's the light coming from? Hollow won't be revealed until you touch it. Lit, dark, open, closed. A symphony of opposites, adjustable and versatile. For spaces that welcome intrigue and personality. It's the light to discover.

Art. Nr. 12170156

### SPECIFICATIONS

Lamp	1x LED Array	
Gear / Transfo	LED gear not incl.	
Cut-out size	ø 146 h 70 (recessed ring)	
Weight	0.27kg	
Min. distance	0.1 m	
IP	IP20	
Glow wire test	960°	
Lifetime	L80 B20 @ 50.000 hrs	
CRI	90	
CIE flux code	92/99/100/100/48	
Power supply	350mA	<b>500mA</b>
	16.4Vf	<b>16.9Vf</b>
Connected load	5.7W	<b>8.5W</b>
Lumen	351lm	<b>474lm</b>
Efficacy	62lm/W	<b>56lm/W</b>
UGR	13	<b>14</b>
Adjustability	h 360° v 90°	
Remark	! must be used with recessed ring	

	WARM WHITE 2700K / CRI 90+	WARM WHITE 3000K / CRI 90+
	LENS 30°	LENS 30°
black struc - black struc	12170056	<b>12170156</b>
black struc - gold	12170032	12170132
black struc - white struc	12170047	12170147
gold - gold	12170087	12170187
white struc - white struc	12170009	12170109



Available label  
<http://supemodular.com/assets/TYPE2.pdf>



## HOLLOW 115 TRIMLESS LED GE

### ACCESSORIES

#### HUE-MODULE

13190130 | HUE DIM CIRCUIT MODULE 150-300W 0/1-10V

#### HUE-BRIDGE

70000616 | HUE BRIDGE EU

70000617 | HUE BRIDGE UK

#### HUE-DEVICE

70000615 | HUE TAP SWITCH

70000154 | NIKO PURE SWITCH FOR HUE - WHITE STEEL

70000155 | NIKO PURE SWITCH FOR HUE - BLACK STEEL

70000152 | HUE DIMMER SWITCH

70008054 | HUE SENSOR

#### CONBOX

10889830 | CONBOX 190X192X130X256

