


MÉDARD RECESSED 70 LED GE

Médard recessed broadens the variety of applications. In contrast to the rest of the family, Médard recessed's light source is fixed, emanating a medium or flood beam angle. Hospitality environments including wellness centers, and high-end residential spaces, including bathrooms, will be spot-on locations for this IP55-rated new family member.

Art. Nr. 11551309

SPECIFICATIONS

Lamp	1x LED Module		
Gear / Transfo	LED gear not incl.		
Cut-out size	ø 65 h 95		
Weight	0.26kg		
Min. distance	0.1 m		
IP	IP55		
Glow wire test	960°		
Lifetime	50000 hrs		
CRI	90		
CIE flux code	100/100/100/100/78		
Power supply	350mA	500mA	700mA
	17.8Vf	18.4Vf	19.3Vf
Connected load	6.2W	9.2W	13.4W
Lumen	450lm	604lm	777lm
Efficacy	73lm/W	66lm/W	58lm/W
UGR	16	17	18
Adjustability	Not Applicable		



Available label
<http://supemodular.com/assets/TYPE2.pdf>

	WARM WHITE 2700K / CRI 90+		WARM WHITE 3000K / CRI 90+	
	MEDIUM 25°	FLOOD 40°	MEDIUM 25°	FLOOD 40°
black struc	11551032	11551132	11551232	11551332
white struc	11551009	11551109	11551209	11551309



MÉDARD RECESSED 70 LED GE

ACCESSORIES

HUE-MODULE

13190130 | HUE DIM CIRCUIT MODULE 150-300W 0/1-10V

HUE-BRIDGE

70000616 | HUE BRIDGE EU

70000617 | HUE BRIDGE UK

HUE-DEVICE

70000615 | HUE TAP SWITCH

70000154 | NIKO PURE SWITCH FOR HUE - WHITE STEEL

70000155 | NIKO PURE SWITCH FOR HUE - BLACK STEEL

70000152 | HUE DIMMER SWITCH

70008054 | HUE SENSOR

