

# FLOS

■ F0263000 Black

## Noctambule Suspension 1 Low Cylinder Bowl

Designed by Konstantin Grcic, 2019




36W - 1007lm - 2700K - CRI> 90

Hanging lamps consisting of interconnecting glass modules reaching a length of 3,2 mt. (126.77") with 4 mt. (157.48") suspended power cable. Cylindrical and semi-spherical transparent blown glass structure, suspended die cast aluminium ring connector, hydroformed steel internal lateral arm and injection moulded optical opal silicone outer ring diffusers. The power supply unit within the ceiling rose can be used as a dimmer to adjust the light intensity by 10% to 100% in either direction by means of the 0-10/1-10V, PUSH, DALI control.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

EAN	8059607000540
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
LED type	LED Module
Power (W)	36
System flux (lm)	1007

### Physical

Colour	Black
Length (mm)	250
Cord length (mm)	4000
Canopy dimension (mm)	45
Canopy width (mm)	187
Net weight (kg)	10.7
Package height (mm)	0
Package width (mm)	0
Package length (mm)	0
Package volume (m3)	0.43
IP internal	20

### Download


Mounting instructions	<a href="#">↓ PDF</a>
Mounting instructions	<a href="#">↓ PDF</a>
Spare Parts	<a href="#">↓ PDF</a>

### Photometric Files


LDT / IES	<a href="#">↓ ZIP</a>
-----------	-----------------------

### Technical Drawings

3D	<a href="#">↓ ZIP</a>
Bim	<a href="#">↓ ZIP</a>



## Schematic light drawing



## Photometric



Lighting type	Total
Light distribution	Symmetric
CCT (K)	2700
CRI>	90

## Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	120-277
LED voltage Vf (Vdc)	null
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



## Spare Parts



- |     |  |           |
|-----|--|-----------|
| 01. | Power supply kit for Arrangements small & Noctambule | RF0410500 |
| 02. | Led dimmer kit                                       | RF0410300 |
| 03. | Noctambule ceiling rose cover                        | RF27422   |
| 04. | Suspension attack                                    | F0253030  |
| 05. | Ring led diffuser                                    | RF27498   |
| 06. | Fixing screws kit                                    | RF0254100 |
| 07. | Noctambule Low Cylinder                              | F0254000  |
| 10. | Noctambule Bowl                                      | F0255000  |

**DOWNLOAD**



RF0410500  
Power supply kit for  
Arrangements small &  
Noctambule



RF0410300  
Led dimmer kit



RF27422  
Noctambule ceiling rose cover



F0253030  
Suspension attack



RF27498  
Ring led diffuser



RF0254100  
Fixing screws kit



F0254000  
Noctambule Low Cylinder



F0255000  
Noctambule Bowl