

5955

Design By Ichiro Iwasaki


The Flat floor lamp offers multiple functionality; material and light are integrated in a single body. The Flat collection contains various planes of light that rise up to become self-illuminating supports.

Model Sheet











47 Green L1



11 Black test ral



37 Terra Red NCS S 4040-Y70R

LED temperature

2700 K / 3500 K / 4000 K

Dimming

Push

Instalation type

Plug-in

Materials

Body: Steel Base: Steel Head: Aluminium Reflector: Aluminum

Light source

1x LED PLATE 7W 400mA



LED

CRI>90 1200 lm 171.4 2700 K / 3500 K / 4000 K

Driver

Constant Current 400 100~240 V V 50~60 Hz HZ

Remarks


24V transformer at plug















Application

Floor Lamps

Packaging

1 Box 0.72 m x 0.72 m x 0.96 m Gross weigth 11.6

Net weigth 3.5 Vol. 0.4976

Lighting effect

General Lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.




Photometric Data

Efficiency Coordinate System **Total Flux** Maximum Value

76.96 lm/W CG 682.09 lm 275.02 cd

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty