moooi

Chalice

EDWARD VAN VLIET



The Chalice Lamp captures the essential grace of glass. Blossoms of tulip-like flowers define the lamp, diffusing light naturally and reflecting the floral pattern enclosed within each chalice.

Detailing



Thanks to the dimmable LED lamps hidden behind the chalices, light is diffused in a natural way and projected by the copper-plated signature flowers.

Colours

Chrome

Metallic Grey

Chalice 24

Dimensions

48cm | 18.9"



Product

24

Packaging

width 48cm | 18.9" неіднт 48cm | 18.9" дертн 48cm | 18.9" діаметег 48cm | 18.9"

WEIGHT NETTO 7kg | 15.43lbs

width $39.3 \, \mathrm{cm} \mid 15.5"$ Height $46.8 \, \mathrm{cm} \mid 18.4"$ Cubage $0.16 \, \mathrm{m}^3 \mid 5.52 \, \mathrm{ft}^3$ Length $85 \, \mathrm{cm} \mid 33.5"$

WEIGHT 20cm | 44.09lbs





Technical CE

MATERIAL

Chromed or powder coated metal sphere, bakelite and glass chalices.

ENERGY LABEL INSTALLATION REQUIRED

Energy Label B Yes

LIGHTSOURCE INCLUDED NUMBER OF LIGHTSOURCES

Yes

 INPUT VOLTAGE
 FREQUENCY

 230
 50/60

MAX POWER CONSUMPTIONDIMMABLE16WYes

LAMPHOLDER COLOUR

LED (Solid state) Transparent with tinned cores

CABLE LENGTH

CANOPY

A O O cm | 157.5"

Brushed steel pebble

400cm | 157.5" Brushed steel pebble

COLOUR TEMPERATUE CRI
2700 K 85

LIGHT OUTPUT 450 lm

Technical cULus

MATERIAL

Chromed or powder coated metal sphere, bakelite and glass chalices.

ENERGY LABEL INSTALLATION REQUIRED

Energy Label B Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

120

MAX POWER CONSUMPTION

16W

LAMPHOLDER

LED (Solid state)

CABLE LENGTH

400cm | 157.5"

COLOUR TEMPERATUE

2700 K

LIGHT OUTPUT

450 lm

NUMBER OF LIGHTSOURCES

24

FREQUENCY

50/60

DIMMABLE

Yes

COLOUR

Transparent with tinned cores

CANOPY

Brushed steel pebble

CRI


85

Chalice 48

Dimensions

61 cm | 24"







Product

WIDTH 61cm | 24"
HEIGHT 61cm | 24"
DEPTH 61cm | 24"
DIAMETER 61cm | 24"
WEIGHT NETTO 7kg | 15.43lbs

Packaging

WIDTH 46.8cm | 18.4"
HEIGHT 57.8cm | 22.8"
CUBAGE 0.34m³ | 12.18ft³
LENGTH 127.5cm | 50.2"
WEIGHT 30cm | 66.14lbs

Technical CE

MATERIAI

Chromed or powder coated metal sphere, bakelite and glass chalices.

ENERGY LABEL

Energy Label B

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

230

INSTALLATION REQUIRED

Yes

NUMBER OF LIGHTSOURCES

48

FREQUENCY

50/60

MAX POWER CONSUMPTION

32W

LAMPHOLDER

COLOUR LED (Solid state) Transparent with tinned cores

CABLE LENGTH

400cm | 157.5" Brushed steel pebble

DIMMABLE

Yes

CANOPY

CRI

85

COLOUR TEMPERATUE 2700 K

LIGHT OUTPUT 900 lm

Technical cULus

MATERIAL

Chromed or powder coated metal sphere, bakelite and glass chalices.

ENERGY LABEL INSTALLATION REQUIRED

Energy Label B Yes

LIGHTSOURCE INCLUDED NUMBER OF LIGHTSOURCES

Yes 48

FREQUENCY **INPUT VOLTAGE** 120 50/60

DIMMABLE MAX POWER CONSUMPTION 32W Yes

LAMPHOLDER COLOUR

LED (Solid state) Transparent with tinned cores

CABLE LENGTH CANOPY

400cm | 157.5" Brushed steel pebble

COLOUR TEMPERATUE CRI 2700 K 85

LIGHT OUTPUT 900 lm

Dimmer

For fluent dimming behaviour we advise a dimmer that is compatible with the following specs.

Please note the functioning of the dimmer and the power supply combination can never be predicted, it always needs to be tested in practice.

DIMMER TYPE

Mains dimmable (trailing edge / reverse phase)

LOAD TYPE

Capacitive load (C-Type)