

# FLOS

03.6613.1C Black/Aluminium

## Light Supply Wall-Washer Trim

Designed by FLOS Architectural, 2015


LED - Phosphor LED - 28W - 1918lm - 4000K - CRI> 80 - Beam° 37



Recessed luminaire with LED light source. Remote 220/240V power supply included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
LED type	Phosphor LED
Lamp category	LED
Iicos	No
Number of heads	1
Power (W)	28
Source flux (lm)	2872
System flux (lm)	1918

### Physical

Colour	Black/Aluminium
Trim	No
Orientation	Fixed
Recessed depth (mm)	290
Net weight (kg)	1.01
IP internal	20
IP external	44

### Download

[Mounting instructions](#)  PDF

### Photometric Files

[LDT / IES](#)  ZIP

### Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



## Schematic light drawing



Beam Angle: 35°

h(m)	E(lx)	D(m)
1	2635	0.70
2	659	1.40
3	293	2.10
4	165	2.79
5	105	3.49

Luminous flux luminaire  
1967 lm (EXTREME CUT OFF)

### Photometric

Lighting type	Indirect, Direct
Light distribution	Asymmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	37
Beam angle C90-270 (°)	52

### Electrical

Insulation class	II
Frequency (Hz)	50/60
Driver	Remote included
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No