

# FLOS

03.6024.B1 White/White

## Kap 80 Surface Round Optic Spot

Designed by FLOS Architectural, 2017




LED - LED array - 9.2W - 739lm - 3000K - CRI> 90 - Beam° 19

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Non dimmable 110/240V.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
LED type	LED array
Lamp category	LED
Ilcos	No
Number of heads	1
Power (W)	9.2
Source flux (lm)	956
System flux (lm)	739

### Physical

Colour	White/White
Trim	No
Orientation	Fixed
Net weight (kg)	0.45
IP internal	20
IP external	20

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)


### Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



## Schematic light drawing



Beam Angle: 19°

h(m)	E(lx)	D(m)
1	2792	0.34
2	698	0.68
3	310	1.02
4	175	1.36
5	112	1.70

## Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	19
Beam angle C90-270 (°)	19

## Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	18.20
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No