

FLOS

03.6614.3B White/White

Light Supply Wall-Washer Trim

Designed by FLOS Architectural, 2015


LED - Phosphor LED - 26W - 1355lm - 3000K - CRI> 98 - Beam° 38



Recessed luminaire with LED light source. Remote 220/240V power supply included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------|---------------------|
| Mounting | Ceiling recessed |
| Environments | Indoor dry location |
| LED type | Phosphor LED |
| Lamp category | LED |
| Ilcos | No |
| Number of heads | 1 |
| Power (W) | 26 |
| Source flux (lm) | 2371 |
| System flux (lm) | 1355 |

Physical

| | |
|---------------------|-------------|
| Colour | White/White |
| Trim | No |
| Orientation | Fixed |
| Recessed depth (mm) | 290 |
| Net weight (kg) | 1.01 |
| IP internal | 20 |
| IP external | 44 |

Download

[Mounting instructions](#) PDF

Photometric Files

[LDT / IES](#) ZIP

Technical Drawings


[2D](#) ZIP

[3D](#) ZIP

[Bim](#) ZIP



Schematic light drawing



Beam Angle: 38°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 1564 | 0.77 |
| 2 | 391 | 1.55 |
| 3 | 174 | 2.32 |
| 4 | 98 | 3.09 |
| 5 | 63 | 3.86 |

Luminous flux luminaire
1355 lm (EXTREME CUT OFF)

Photometric

| | |
|------------------------|------------------|
| Lighting type | Indirect, Direct |
| Light distribution | Asymmetric |
| CCT (K) | 3000 |
| CRI> | 98 |
| Beam angle C0-180 (°) | 38 |
| Beam angle C90-270 (°) | 52 |

Electrical

| | |
|--------------------|-----------------|
| Insulation class | II |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 220.00 |
| Driver | Remote included |
| Dimmable | No |
| Dimming type | Non Dimmable |
| Emergency type | No |