

FLOS

03.9730.40A White/White/White

Light Shadow Surface 4 Spots Optic Medium

Designed by FLOS Architectural




LED - Power LED - 10.8W - 793lm - 3000K - CRI> 90 - Beam° 22

Surface luminaire with 4 LED lighting spots. Power source 220-240V incorporated.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------|---------------------|
| Mounting | Surface |
| Environments | Indoor dry location |
| LED type | Power LED |
| Lamp category | LED |
| Iicos | No |
| Number of heads | 1 |
| Power (W) | 10.8 |
| Source flux (lm) | 1140 |
| System flux (lm) | 793 |

Physical

| | |
|-----------------|-------------------|
| Colour | White/White/White |
| Trim | No |
| Orientation | Fixed |
| Length (mm) | 146 |
| Net weight (kg) | 0.80 |
| IP internal | 44 |
| IP external | 44 |

Download

Mounting instructions [↓ PDF](#)

Photometric Files


LDT / IES [↓ ZIP](#)

Technical Drawings

[🔒 Bim](#) [↓ ZIP](#)



Schematic light drawing



Beam Angle: 22°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 5302 | 0.39 |
| 2 | 1325 | 0.78 |
| 3 | 589 | 1.17 |
| 4 | 331 | 1.56 |
| 5 | 212 | 1.95 |

Photometric

| | |
|------------------------|-----------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 3000 |
| CRI> | 90 |
| Beam angle C0-180 (°) | 22 |
| Beam angle C90-270 (°) | 22 |

Electrical

| | |
|-----------------------------------|--------------|
| Insulation class | I |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 220.00 |
| Alternating current voltage (Vac) | 230 |
| LED voltage Vf (Vdc) | 12 |
| Driver | Integrated |
| Dimmable | No |
| Dimming type | Non Dimmable |
| Emergency type | No |