

GUISE

Design by Stefan Diez.

Reference

2277.

Application

Hanging lamps

Installation type

Surface

Description

Vibia presents a pendant lamp with a horizontal glass piece where the light source is invisible, emanating directly from the material.

Diffuser

Difusor de vidrio borosilicato transparente

Materials

Profile: Aluminum


Diffuser: Borosilicate glass

Finish



2277-18 Matt graphite lacquer (ADAPTA RF 9913 WX)

Sketch



Electrical characteristics



Led 3000K CRI >90 2613 lm 87 lm/W

Fixture: 1158.86 lm 30.9 lm/W

Driver included: CC - Constant Current 110-240V 50/60Hz

Electronic dimming OPTICAL SENSOR

Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.1470 m³ /

Gross weight 9.5 kg. / Net weight 7.5 kg.


Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 1

Coordinate system : CG

Total flux : 1158.86 lm

Maximum value : 185.32 cd/klm

Light position : C=0.00 G=10.00

Isolux : Isolux (Floor)

Light position :

X=0.00ft Y=0.00ft Z=8.20ft

Certificates

