

FLOS

03.6273.06DCB Chrome

Find Me 1 Suspension Casambi integrated NEW

Designed by FLOS Architectural, 2020



Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
LED type	Power LED
Lamp category	LED
Ilcos	No
Bulb finish	Clear
Number of heads	1
Power (W)	8
System power (W)	8.4
Source flux (lm)	482
System flux (lm)	365
Efficacy (lm/W)	43.45

Physical

Colour	Chrome
Trim	No
Orientation	Fixed
Length (mm)	130
Net weight (kg)	0.3
IP internal	20
IP external	20



Download

Mounting instructions [↓ PDF](#)

Photometric Files


LDT / IES [↓ ZIP](#)

Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[↓ ZIP](#) Bim



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50
Beam angle C0-180 (°)	14
Beam angle C90-270 (°)	14
UGR _L	4

Electrical

Insulation class	III
Main voltage (Vac)	24
Forward voltage (V)	24
Driver	Remote excluded
Dimmable	Yes
Dimming type	Dimmable Casambi
Dimming range (%)	1-100

Notes

Maximum 21 spots for a single driver. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.