

FLOS

03.8957.40A White/White/Black

Light Shadow Surface 4 Spots Optic Spot

Designed by FLOS Architectural




LED - Power LED - 10.8W - 724lm - 2700K - CRI> 90 - Beam° 10

Surface luminaire with 4 LED lighting spots. Power source 220-240V incorporated.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Surface
Environments	Indoor dry location
LED type	Power LED
Lamp category	LED
Ilcos	No
Number of heads	1
Power (W)	10.8
Source flux (lm)	1080
System flux (lm)	724

Physical

Colour	White/White/Black
Trim	No
Orientation	Fixed
Length (mm)	146
Net weight (kg)	0.80
IP internal	44
IP external	44

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

[🔒 Bim](#) [↓ ZIP](#)



IP	GWT	IP
44	850°	44

Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	10
Beam angle C90-270 (°)	10

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220.00
Alternating current voltage (Vac)	230
LED voltage Vf (Vdc)	12
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No