

FLOS



03.8937.14A Black/Black

Light Shadow Adjustable No Trim 8 Spots Optic Spot


Designed by FLOS Architectural



Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------|---------------------|
| Mounting | Ceiling recessed |
| Environments | Indoor dry location |
| LED type | Power LED |
| Lamp category | LED |
| Iicos | No |
| Number of heads | 1 |
| Power (W) | 21.6 |
| Source flux (lm) | 2280 |
| System flux (lm) | 1830 |

Physical

| | |
|--------------------------|-------------|
| Colour | Black/Black |
| Trim | No |
| Orientation | Adjustable |
| Longitudinal tilting (°) | 30 |
| Recessed depth (mm) | 75 |
| Length (mm) | 289 |
| Net weight (kg) | 0.50 |
| IP internal | 20 |
| IP external | 20 |

Download

[Mounting instructions](#) ZIP

Photometric Files

[LDT / IES](#) ZIP

Technical Drawings


[2D](#) ZIP

[3D](#) ZIP

[Bim](#) ZIP



Schematic light drawing



Beam Angle: 10°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 33034 | 0.18 |
| 2 | 8259 | 0.36 |
| 3 | 3670 | 0.54 |
| 4 | 2065 | 0.72 |
| 5 | 1321 | 0.90 |

Luminous flux Luminaire
1830 lm (EXTREME CUT OFF)

Photometric

| | |
|------------------------|-----------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 3000 |
| CRI> | 90 |
| Beam angle C0-180 (°) | 10 |
| Beam angle C90-270 (°) | 10 |

Electrical

| | |
|-----------------------------------|-----------------|
| Insulation class | II |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 220.00 |
| Alternating current voltage (Vac) | 230 |
| LED voltage Vf (Vdc) | 24 |
| Driver | Remote included |
| Dimmable | No |
| Emergency type | No |

Notes

It requires a pre-installation frame, to be ordered separately.

Accessories & Power Supply




REQUIRED
Frame

Installation

08.0517.00

Pre-installation No Trim Frame 8L
Fix Adjustable



OPTIONAL
Accessory

Mounting

08.0059.90

Accessory for mounting of No
Trim Adjustable continuous line.