





WINK ASY 82 LED SPREADLIGHT GE

Wink may be recessed, and therefore discreet, but its technical ingenuity is nothing short of remarkable, so is its sense of humour. As its name suggests, it likes to wink at you. The streamlined design, where elegance meets high-quality finish, results in a fixture that is half hidden in the ceiling and half peeking out. It has all the features to become a new Modular icon. With the debut of the Wink 82, we are also presenting a completely new Wink accessory: Wink flange. Compatible with all 3 Wink lamps, Wink flange adds an extra accent in the form of a low ring around the spot, rather than a completely seamless install. Its precision-designed conical shape complements the spot, enabling it to have a quiet conversation with the ceiling.

SPECIFICATIONS		
Lamp	1x LED Array	
Gear / Transfo	LED gear not	incl.
Cut-out size	ø 98 h 100 (W	/ink Flange) or ø 111 h 100
	(Recessed rin	
Weight	0.29kg	
Min. distance	0.1 m	
IP	IP54	
Glow wire test	960°	
Lifetime	L80 B20 @ 50	.000 hrs
CRI	90	
Power supply	350 mA	500mA
	17.8Vf	18.4Vf
Connected load	6.2W	9.2W
Lumen	3291m	4421m
Efficacy	531m/W	48lm/W
UGR	28	29
Adjustability	h 360°	
Remark	! must be used	d with recessed ring or flang
	! LED light is i	inserted at a 30° angle
MODULAK Tota familiaria LE A A A A A B C D E The lamps cannot be Lotaged in the lumnate.	Available http://supi	· label emodular.com/assets/TYPE2.pdf
874/2012 CCO	♠ ♠	

	WARM WHITE 2700K / CRI 90+	WARM WHITE 3000K / CRI 90+
black struc	14202032	14202132
white struc	14202009	14202109

webterm_footertext 1/2

Art. Nr.14202132

WINK



WINK AS	Y 82 LED SPREADLIGHT GE	
ACCESSORIE		
HUE-BRIDGE		
70000616	HUE BRIDGE EU	
	ĺ	
HUE-DEVICE		
70000152	HUE DIMMER SWITCH	
70000615	HUE TAP SWITCH	
70008054	HUE SENSOR	