



WEVER & DUCRÉ
LIGHTING

STRANGE 1.0 PAR16

131120W0

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Recessed

Tilt min 35°

Tilt max 35°

Rotation 355°

White Matt

RAL 9003^a

Below IP20

Interior

480^b to 520° lm

LED

Lamp PAR16

PAR16

Socket GU10

max. 12 W

CRI ≥ 90

OPTICAL

Wide Flood

Beam angle 48°

ELECTRICAL

100 - 240 V

LED Inset 6.5 W

Class 2

Safety distance 0.3 m

PHYSICAL

Length 70 mm

Width 70 mm

Height 115 mm

0.41 kg

CUTOUT

Length 86 mm

Width 86 mm

Min. ceiling thickness 8 mm


Max. ceiling thickness 32 mm

Recessed depth 120 mm


^a Color may deviate slightly due to production conditions.

^b PAR16 LAMP 2700K CRI90


^c PAR16 LAMP 3000K CRI90



Squared ceiling recessed luminaire made from aluminium; RAL 9003; recessed depth 120 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; 355° rotatable and 35° tiltable; degree of protection IP20; PC2; lamp not included;



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

STRANGE 1.0 PAR16

131120W0

CONE DIAGRAM

wide flood 48°

h (m)	EO° (lx)	ø (m)
1	768	0.89
2	192	1.78
3	85	2.66
4	48	3.55
5	31	4.44

OTHER

Metal spring clip

TYPE	(MM)	ORDERCODE
MR16 LED PAR16 max. 12W	59	9 0 0 1 9 7 0 0



ø59

Spring clip

TYPE	COLOUR	(MM)	ORDERCODE
MR16 LED PAR16 max. 12W	Black	59	9 0 0 1 9 8 B 0
MR16 LED PAR16 max. 12W	Gold	59	9 0 0 1 9 8 G 0
MR16 LED PAR16 max. 12W	Bronze	59	9 0 0 1 9 8 Q 0
MR16 LED PAR16 max. 12W	Silver	59	9 0 0 1 9 8 S 0
MR16 LED PAR16 max. 12W	White	59	9 0 0 1 9 8 W 0

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	ø50 · 58	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	ø50 · 58	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	ø50 · 58	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	ø50 · 58	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	ø50 · 52	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	ø50 · 52	9 0 5 2 2 7 S 4

MOUNTING

Plasterkit

TYPE	L · W · H (MM)	ORDERCODE
STRANGE 1.0 SNEAK TRIMLESS 1.0	83 · 83 · 48	9 0 0 1 7 1 2 0