

# FLOS

03.4162.B1 White

## Easy Kap Ø 80 Adjustable


Designed by FLOS Architectural, 2016



Recessed luminaire with main voltage source. Installation frame not necessary.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	Bulb
Lamp category	LED retrofit
Lamp type	PAR16
Lamp holders	GZ10
Ilcos	No
Number of heads	1
System power (W)	50

### Physical

Colour	White
Trim	Yes
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	20
Transversal tilting (°)	20
Recessed depth (mm)	155
Spot diameter (mm)	80
Net weight (kg)	0.12
IP internal	20
IP external	23

### Download


Mounting instructions

[↓ PDF](#)

### Ecodesign and Energy Labelling



Replaceable (LED only) light source by an end-user



## Photometric

Lighting type	Direct
Light distribution	Symmetric

## Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	230
LED current (mA)	-9
Emergency type	No

## Notes

Not suitable for lens accessories.

---