

FLOS

03.1226.DR Anthracite

C1 Mono Spot Ceiling Small Ø 35

Designed by Vincent Van Duysen, 2020




LED - Power LED - 6W - 374lm - 3000K - CRI> 90 - Beam° 18

Adjustable luminaire with LED for indoor use, suitable for wall installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location. The installation frame must be ordered separately.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)




Main specifications

Mounting	Ceiling
Environments	Indoor dry location
LED type	Power LED
Lamp category	LED
Power (W)	6
System flux (lm)	374

Physical

Colour	Anthracite
Orientation	Adjustable
Rotation (°)	355
Longitudinal tilting (°)	60
Spot diameter (mm)	35
Net weight (kg)	0.18
IP internal	20
IP external	20

Download

[Mounting instructions](#)  PDF

Photometric Files

[LDT / IES](#)  ZIP

Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	18
Beam angle C90-270 (°)	18

Electrical

Insulation class	III
LED current (mA)	500
Driver	Remote excluded
Dimmable	Yes
Emergency type	No

Accessories & Power Supply



REQUIRED
Frame

08.0208.00

No Trim installation frame for ceiling mounting



REQUIRED
Accessory

08.0211.DR

Coated aluminum mount for surface installation (ceiling)



REQUIRED
Accessory

08.0211.DY

Coated aluminum mount for surface installation (ceiling)



REQUIRED
Accessory

08.0211.EQ

Coated aluminum mount for surface installation (ceiling)



REQUIRED
Accessory

08.0211.ER

Coated aluminum mount for surface installation (ceiling)



REQUIRED
Accessory

08.0211.ES

Coated aluminum mount for surface installation (ceiling)



REQUIRED
Power supply

Electrical

60.9207

Continuous current power supply, dimmable Casambi, 220/240V - 50/60Hz, 300mA - 16W / 350mA - 18,5W / 400mA - 21,5W / 450 mA - 24W / 500mA - 27W / 600mA - 32W / 650 mA - 35W / 700 mA - 36W /750 /800 /900 /1000 /1050 /1200 mA - 38W.



REQUIRED
Power supply

Electrical

60.9186

Continuous current supply source of 240V - 50/60Hz with dimmable Dali 2, push dimming. 300mA - 16W / 350mA - 18W / 400mA - 21W / 500mA - 27W / 600mA - 32W / 650 mA - 35W / 700 / 750 / 800 / 900 / 1000 / 1050 mA - 36W



REQUIRED
Power supply

Electrical

60.9592

Non dimmable continuous current power supply. 15-30W, 220/240V -50/60Hz with power current selected through adjustable switch. 350mA - 15W / 400mA - 17W / 450mA - 19W / 500mA - 22W / 550mA - 24W / 600mA - 26W / 650mA - 28W / 700mA - 30W.



REQUIRED
Power supply

Electrical

60.9208

Continuous current power supply of 13-20W - Dim 1-10V&Push - 110/240V - 50/60Hz with power current selected through adjustable