



SPECIFICATION

| | |
|------------------------|---|
| TYPE | Constant voltage |
| DRIVER CURRENT | N/A |
| DRIVER VOLTAGE | 12V |
| DIMMABLE | NON-DIMMING |
| ELECTRICAL CLASS | CLASS 2 |
| SUPPLY VOLTAGE | 90-264V AC |
| SUPPLY FREQUENCY | 47/63Hz |
| POWER FACTOR | N/A |
| MIN. OUTPUT VOLTAGE | N/A |
| MAX. OUTPUT VOLTAGE | 12.0V DC |
| MIN. OUTPUT CURRENT | 0.00A |
| MAX. OUTPUT CURRENT | 1.67A |
| INRUSH CURRENT | COLD START 70A (twidh=215µs measured at 50% Ipeak) |
| IP RATING | IP67 |
| WORKING TEMPERATURE | -30°C - +70°C |
| CONNECTION TYPE | Trailing wires |
| LENGTH | 118mm |
| WIDTH | 35mm |
| HEIGHT | 26mm |
| MIN. CIRCULAR APERTURE | 48mm/1-7/8" |
| MAX. LED DISTANCE | 600mm 18AWG |
| MANUFACTURER | Mean well |
| MODEL NUMBER | LPV-20-12 |

To calculate product compatibility, visit the driver calculator on each product page on the Astro website.

See the Astro website for installation guides.